

This product may be hard wired to the door operator or connected to BEA's line of wireless transmitters.

Compatible with both surface and flush mount boxes



BEA, Inc. **RIDC Park West** 100 Enterprise Drive Pittsburgh, PA 15275-1213 www.BEAinc.com

Customer Service: 800.523.2462 Technical Support: 800.407.4545

APPLICATIONS



TECHNICAL SPECIFICATIONS

Faceplate Material	16 gauge, 304 2B Stainless Steel
Backplate Material	1/8 inch thick, Aluminum
Mounting Screws	Stainless Steel, 6-32 × 1 in & 8-32 × 1 in Allen Head Size: $\frac{5}{64}$
Cherry Switch	Single-pole, 15 A, COM / NO / NC, UL Recognized
Compatible Wireless Frequencies	900, 433 or 300 MHz

DIMENSIONAL DRAWINGS





RELATED PRODUCTS





10PBR1 "PUSH TO OPEN" TEXT & HANDICAP LOGO

3

PUSH O OPE

10PBR1AL

"PUSH TO OPEN"

TEXT & ALTERNATE

HANDICAP LOGO



10PBRLL HANDICAP LOGO ONLY

PUSH TO OPEN

10PBS6 "PUSH TO OPEN"

TEXT ONLY



"PUSH TO OPEN"

TEXT ONLY

10PBR10 PLAIN FACE





10PBS610 PLAIN FACE

10PBS61 "PUSH TO OPEN" TEXT & HANDICAP LOGO

10PBS6LL HANDICAP LOGO ONLY



20181211

6 INCH ROUND & SQUARE PUSH PLATES STAINLESS STEEL ACTUATORS

BEA, Inc. **RIDC Park West** 100 Enterprise Drive

Customer Service: 800.523.2462 Pittsburgh, PA 15275-1213 Technical Support: 800.407.4545





79.0099.07