

DELAYED EGRESS MAGLOCK KIT

UL LISTED ALL-IN-ONE KIT WITH MAGLOCK, SOUNDER AND KEYSWITCH



PRIMARY APPLICATIONS



DESCRIPTION

BEA's Delayed Egress Maglock Kit is a user friendly security solution for out-swinging perimeter doors. The kit meets a variety of building, fire and life safety codes.

A 1200 lb, pressure-sensing maglock is coupled with a keyswitch and sounder to create an easy-to-install solution that controls and monitors door access.

The keyswitch can be positioned in a convenient location to create authorized personnel access points.

Note: Not intended for outdoor environments

FEATURES & BENEFITS

- Double door (2 single doors) can be synchronized
- Authorized egress time programmable 0 – 15 seconds
- Selectable 30 second door prop alarm
- LED color and flashes can be customized
- Monitored fire alarm input
- Delayed Egress can be triggered with pressure on the door or with a REX input (or disabled completely)
- UL 294 listed



BEA, Inc.
RIDC Park West
100 Enterprise Drive
Pittsburgh, PA 15275-1213

Customer Service: 800.523.2462
Technical Support: 800.407.4545
www.BEAinc.com


TECHNICAL SPECIFICATIONS

Housing Dimensions	10.8125 in (W) x 2.875 in (H) x 2.125 in (D)
Armature Dimensions	7.4375 in (W) x 2.375 in (H) x 0.625 in (D)
Voltage / Tolerance	12 – 24 VDC; $\pm 10\%$
Max. Power / Current Draw	
Maglock & Sounder	0.49 A / 12 VDC 0.24 A / 24 VDC
Low Voltage Supply Detection / Alarm	< 8 V
Holding Force	Up to 1200 lb
Mortise Cylinder	1.125 in cylinder with straight cam required, NOT INCLUDED Requires Part 10CYLINDERKA or 10CYLINDERKD
Operating Temperature	14 °F – 140 °F
Norm Conformance	UL / CUR Listed FWAX Special locking arrangements
Compliance Provisions	IBC, SBC, UBC, BOCA, or NBC of Canada, NFPA 101


RELATED PRODUCTS



10MAGDE1
DELAYED EGRESS
MAGLOCK KIT



10CYLINDERKA
MORTISE CYLINDER,
KEYED ALIKE



10CYLINDERKD
MORTISE CYLINDER,
KEYED DIFFERENT



10KEYPADU
UNIVERSAL
KEYPAD



10KEYPADUSL
UNIVERSAL SLIM-LINE
KEYPAD



10PS12-24
110-1224 VAC
POWER SUPPLY

