



PHOENIX EX™

MOTION SENSOR WITH EXPLOSION-PROOF /
FLAME-PROOF HOUSING FOR INTRUSTION PROTECTION



PRODUCT



[Go to the product page](#)

TECHNOLOGY



CERTIFICATIONS



DESCRIPTION


BEA's **PHOENIX EX™** combines a microwave activation sensor in an explosion-proof / flame-proof housing, which is ideal for use in unique environments such as chemical manufacturing, petroleum refining and military facilities.

The **PHOENIX EX™** is designed to detect within a desired area for security, warning indication and automation. When tied into a security system, the **PHOENIX EX™** offers a monitoring feature via the end-of-line resistors. These resistors provide

unique output states, which allow differentiation between an activation signal and an interruption in functionality due to tampering of the device.

The explosion-proof / flame-proof housing is a water-proof rated enclosure designed as an IP66 housing. This housing achieves UL Class I, Div. 1, Groups B, C, D; Class II, Div. 1 & 2, Groups E, F, G; and Class III***.

***Adalet / Scott Fetzer Co., UL Listing #E81696




Energy Savings

Bidirectional, unidirectional approach and unidirectional depart microwave detection options

Vandal Resistant

Integrated tamper alert switch and end-of-line resistors




Certified Housing

Explosion-proof / flame-proof housing weighs 10 pound housing


Select Your Angle

Tilt adjustment angle: -90 to 30° in elevation


APPLICATIONS



Military Bunkers



Munitions Storage



Compressor Station

TECHNICAL SPECIFICATIONS

Technology	Microwave Doppler Radar
Transmitter Frequency	24.150 GHz
Transmitter Radiated Power	< 20 dBm EIRP
Transmitter Power Density	< 5 mW / cm ²
Detection Mode	Motion
Anti-Tamper Feature	Tamper alert via output
Detection Zone	
PHOENIX EX	13' × 16' @ 16'
PHOENIX EX XL	13' × 16½' @ 8½'
PHOENIX EX WIDE	30' × 11' @ 21'
	Typical at 30° and field size 9
Output*	Relay (free of potential change-over contact)
Maximum Contact Voltage	42 VAC / VDC
Maximum Contact Current	1 A (resistive)
Maximum Switching Power	30 W (DC); 60 VA (AC)
Minimum Detection Speed	2 in / s*
Supply Voltage	12 – 24 VAC; ±10% 12 – 24 VDC; 30% / -10%
Mains Frequency	50 – 60 Hz
Maximum Power Consumption	< 2 W
Electrical Access	¾"
Cable Length	30' or 100' (default)
Mounting Height	
PHOENIX EX	11½ – 23'
PHOENIX EX XL	6½ – 11½'
PHOENIX EX WIDE	11½ – 21'
Dimensions	
Housing & Bracket	5½" (H) × 7½" (W) × 9" (L)
Weight	10 lbs
Temperature Range	-22 – 140 °F
Housing Certification***	See User's Guide
Norm Conformity	EMC: 2004 / 108 / EC R&TTE: 1999 / 5 / EC

*Measured in optimal conditions

**Output ratings may vary depending on optional end-of-line resistor values

***Adalet / Scott Fetzer Co., UL Listing #E81696

PRODUCT SERIES



10PHOENIXEX
Standard mounting heights



10PHOENIXEXXL
Low mounting heights



10PHOENIXEXW
Wide detection fields



10REMOTE
BEA universal remote control

DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company