



# PNEUMATIC PUSH BUTTONS

ACCESS CONTROL PUSH BUTTON  
WITH MECHANICAL PNEUMATIC HOLD TIME

## PRODUCT



[Go to the product page](#)

## DESCRIPTION

BEA's **PNEUMATIC PUSH BUTTONS** are ruggedized, including stainless steel faceplates and colored, anodized aluminum buttons, appropriate for most indoor applications.

The device is uniquely designed to minimize the number of moving parts, in turn reducing the wear and tear of the button and extending the life of the device.



Upon activation, the user-defined time delay initiates without additional mechanical action or the need of external power.

## Customizable

Adjustable time delay of 2 – 60 seconds

## Standards Compliant

Listed UL 508 / CSA C22.2 No 14-10 with MET LABS, File #E113051

## Various Styles

Buttons available in 1 5/8 inch (standard) or 2 inch (large) sizes


## Meet Your Application Needs

Available in a variety of combinations of color, text and logo upon request

## Tested To Last

Tested to perform greater than 1 million operations

## APPLICATIONS



Request-To-Exit

## TECHNICAL SPECIFICATIONS

<b>Technology</b>	Pneumatic
<b>Faceplate Dimensions</b>	
Single	2 3/4" (W) x 4 1/2" (H)
Jamb	1 3/4" (W) x 4 1/2" (H)
<b>Visual Style</b>	Red Button with "Push to Exit" text Blue Button with Handicap Logo Green Button with "Push to Exit" text
<b>Materials</b>	Stainless steel faceplate with colored, anodized aluminum button
<b>Switch Rating</b>	5 A @ 125 VAC
<b>Time Range</b>	2 – 60 s ±15%, adjustable
<b>Repeat Accuracy</b>	±5% @ 72 °F
<b>Operating Temperature</b>	Rated for indoor use only -15 – 120 °F
<b>Timer Life</b>	1 million operations

## PRODUCT SERIES



### 10ACPBDA1

2" Jamb, Red button,  
Text only



### 10ACPBDA2

2" Single, Red button,  
Text only



### 10ACPBDA3

1 1/2" Jamb, Red button,  
Text only



### 10ACPBDA4

1 1/2" Single, Red button,  
Text only



### 10ACPBDA5

2" Jamb, Blue button,  
Logo only



### 10ACPBDA6

2" Single, Blue button,  
Logo only



### 10ACPBDA7

1 1/2" Jamb, Blue button,  
Logo only



### 10ACPBDA8

1 1/2" Single, Blue button,  
Logo only



### 10ACPBDA9

2" Jamb, Green button,  
Text only



### 10ACPBDA10

2" Single, Green button,  
Text only



### 10ACPBDA11

1 1/2" Jamb, Green button,  
Text only



### 10ACPBDA12

1 1/2" Single, Green button,  
Text only



### 10BOX24SGSM

Single surface mount



### 10BOXJAMBST

Jamb surface mount

**DISCLAIMER** Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

[WWW.BEASENSORS.COM](http://WWW.BEASENSORS.COM)



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA  
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company