


# U BRACKET

Glass door mounting kit for MAGLOCKS



Visit website for available languages of this document.



1. Place the steel bushing and rubber bushing according to the drawing.
2. Use the 3 set screws to clamp the glass firmly. A suitable threadlock should be applied to all fixing screws.
3. Insert the aluminum bar and attach armature plate. The aluminum bar can be adjusted so that it matches the MAGLOCK.

**NOTE:** Do not overtighten the mounting screw of the armature plate. Allow floating movement for maximum holding force.

## BEA, INC. INSTALLATION/SERVICE COMPLIANCE EXPECTATIONS

BEA Inc., the sensor manufacturer, cannot be held responsible for incorrect installations or incorrect adjustments of the sensor/device; therefore, BEA Inc. does not guarantee any use of the sensor/device outside its intended purpose.

BEA Inc. strongly recommends that installation and service technicians be AAADM-certified for pedestrian doors, IDA-certified for doors/gates, and factory-trained for the type of door/gate system.

Installers and service personnel are responsible for executing a risk assessment following each installation/service performed, ensuring that the sensor/device system performance is compliant with local, national, and international regulations, codes, and standards.

Once installation or service work is complete, a safety inspection of the system shall be performed and documented per the manufacturer's recommendations or industry guidelines. Examples of compliance may apply to ANSI 156.10, ANSI 156.19, ANSI/DASMA 102, ANSI/DASMA 107, UL294, UL325, and International Building Code.

Tech Support: 1-800-407-4545

Customer Service: 1-800-523-2462

General Tech Questions: [techservices-us@BEAsensors.com](mailto:techservices-us@BEAsensors.com)  
[www.BEAsensors.com](http://www.BEAsensors.com)



A Halma company