



EAGLE ARTEK

COMPACT, MOTION SENSOR FOR AUTOMATIC DOORS



LEARN MORE



click or scan

TECHNOLOGY



CERTIFICATIONS



DESCRIPTION

BEA's **EAGLE ARTEK** is a motion sensor for all types of automatic doors. Its slim and compact design ensures discreet integration for your application..

EAGLE ARTEK offers superior field performance with improved filters that help to reduce false detections that lead to increased energy costs.

This sensor is easy to install and set up with flexible parameters and simple push-button settings. Unlike legacy sensors, the detection field shape can be adjusted without changing the antenna manually.

A variety of installation accessories are available, making the **EAGLE ARTEK** a convenient activation solution for any environment.




Compact and Attractive Design

Slim and compact design permits integration with all types of automatic door operators

Easy to Use

Electronic management of the radar field shape and push-button adjustments allow for quick installation and setup




Energy Efficient

Immunity Filter, Field Size, and Field Shape settings work together with direction sensing capability (Detection Mode) to reduce door open time

Easy to Retrofit

Same mounting references and plug-in interface accessory make it easy to retrofit EAGLE

APPLICATIONS



Simultaneous Pair



Revolving

TECHNICAL SPECIFICATIONS

TECHNOLOGY / PERFORMANCE

Technology	microwave
Detection mode	motion
Transmitter frequency:	24.15 GHz
Transmitter radiated power:	< 20 dBm EIRP
Transmitter power density:	< 5 mW/cm ²
Max. detection range:	wide: 13' x 6.5' narrow : 6.5' x 7' (@ 7' high)
Min. detection speed:	2 in/s

ELECTRICAL

Supply voltage*:	12 – 24 VAC ±10% (50 – 60 Hz) 12 – 24 VDC +30% / -10%
Max. power consumption:	< 1 W
Output*:	solid-state relay (free of polarity)
Max. switching voltage:	30 VAC / 42 VDC
Max. switching current:	100mA (resistive)

PHYSICAL

Mounting height:	6 – 13'
Tilt angles:	0 – 90° vertical -30 – 30° lateral
Temperature range:	-4 – 131 °F (-20 – 55 °C)
Dimensions:	4.72" (L) x 1.96" (H) x 1.96" (W)
Material:	ABS
Weight:	120 g
Cable length:	8'

COMPLIANCE

Degree of protection:	IP54
FCC certification:	FCC: G9B-100606 IC: 4680A-100606

* External electrical sources must be within specified voltages, max 100 W, and ensure double insulation from primary voltages

PRODUCT SERIES



10EAGLEARTEK
Microwave motion sensor

ACCESSORIES



10EARA
Rain accessory



10EACA
Ceiling accessory (white)



10EACA-BLK
Ceiling accessory (black)



10EABA
Bracket accessory



35.0303
Replacement cover (black)



35.0319
Replacement cover (white)



35.0320
Replacement cover (silver)

RELATED PRODUCTS



10LZRFLATSCAN3D-SWBK
LZR-FLATSCAN 3D SW sensor kit (black)



10LZRFLATSCAN-SWB
LZR-FLATSCAN SW full-energy kit (black)



10LZRMICROSCAN1T
Single swing-door kit



10LZRMICROSCAN2T
Simultaneous pair / dual egress kit



10BR3X
Programmable 3-relay logic module



10REMOTE
Universal remote control



10PSMDR2024
DIN rail power supply, 100 – 240 VAC / 24 VDC



10PSST242
Plug-in power supply



1024VAC
24 VAC transformer with mounting feet

DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company