



IXIO-ST INDUSTRIAL

PRESENCE SENSOR FOR SMALL
INTERIOR INDUSTRIAL DOORS


DESCRIPTION

BEA's **IXIO-ST INDUSTRIAL** is an effective, versatile and easy-to-use presence sensor for interior industrial doors, automatic sliding doors and off-door industrial automation. It can be used for both clear door openings and side-lite protection.


Precise infrared curtains coupled with visible alignment beams make the **IXIO-ST INDUSTRIAL** extremely safe and easy to adjust. This state-of-the-art sensor features an on-board LCD screen that streamlines the installation and setup processes.

The **IXIO-ST INDUSTRIAL** has earned a comprehensive list of credentials and certifications, including FCC and IP54.

APPLICATIONS




Industrial Doors



Dual Slide with Sidelite Protection

DIMENSIONES



TECHNICAL SPECIFICATIONS

TECHNOLOGY / PERFORMANCE

Detection mode:	Presence typical response time: < 200 ms (max: 500 ms)
Technology:	Active infrared with background analysis Spot: 2" x 2" (typ) Number of spots: max. 24 per curtain Number of curtains: 2
Mounting height:	6'6" – 11'6" local regulations may impact acceptable mounting height (pedestrian applications only)
Sensor temperature range:	-13 – 131 °F * 0 – 95% relative humidity, non-condensing LCD screen is operational from 14 – 131 °F. The sensor may still be programmed in colder temperatures, but with the remote control.

ELECTRICAL

Output:	
Relay 1	Electromechanical relay (potential and polarity free) Max. contact current: 1 A Max. contact voltage: 30 VAC Adjustable hold time: 0.5 – 9 s
Relay 2	Solid-state relay (potential and polarity free) Max. contact current: 100 mA Max. contact voltage: 42 VDC / 30 VAC
Test/Monitoring input:	Sensitivity: Low: < 1 V High: > 10 V (max. 30 V) Response time on test request: typical < 5 ms
Supply voltage*:	12 – 24 VAC ±10% 12 – 30 VDC ±10% to be operated from SELV-compatible power supplies only
Power consumption:	< 1.5 W
Noise:	< 70 dB
PHYSICAL	
Degree of protection:	IP54
COMPLIANCE	
Compliance:	ISO 13849 PL «c» CAT. 2 (under the condition that the door control system monitors the sensor at least once per door cycle)

* External electrical sources must be within specified voltages and ensure double insulation from primary voltages

DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company