



IXIO-ST

PRESENCE SENSOR FOR
AUTOMATIC INDUSTRIAL DOORS


DESCRIPTION

BEA's **IXIO-ST** is an effective, versatile and easy-to-use presence sensor for automatic sliding doors. It can be used for both clear door openings and side-lite protection.

Precise infrared curtains coupled with visible alignment beams make the **IXIO-ST** extremely safe and easy to adjust. This state-of-the-art sensor features an on-board LCD screen that streamlines the installation and setup processes.


The **IXIO-ST** can be adjusted into an ANSI compliant solution and has earned a comprehensive list of credentials and certifications, including FCC and IP54.

APPLICATIONS



Dual Slide with Sidelite Protection

DIMENSIONS



TECHNICAL SPECIFICATIONS

TECHNOLOGY / PERFORMANCE

Detection mode	Presence typical response time: < 200 ms (max: 500 ms)
Technology	Active infrared with background analysis Spot: 2" x 2" (typ) Number of spots: max. 24 per curtain Number of curtains: 2
Mounting height:	6'6" – 11'6" local regulations may impact acceptable mounting height (pedestrian applications only)
Sensor temperature range:	-13 – 131 °F * 0 – 95% relative humidity, non-condensing LCD screen is operational from 14 – 131 °F. The sensor may still be programmed in colder temperatures, but with the remote control.

ELECTRICAL

Output

Relay 1	Electromechanical relay (potential and polarity free) Max. contact current: 1 A Max. contact voltage: 30 VAC Adjustable hold time: 0.5 – 9 s
Relay 2	Solid-state relay (potential and polarity free) Max. contact current: 100 mA Max. contact voltage: 42 VDC / 30 VAC

Test/Monitoring input:	Sensitivity: Low: < 1 V High: > 10 V (max. 30 V) Response time on test request: typical < 5 ms
-------------------------------	---

Supply voltage:	12 – 24 VAC ±10% 12 – 30 VDC ±10% to be operated from SELV-compatible power supplies only
------------------------	---

Power consumption:	< 2.5 W
---------------------------	---------

Noise:	< 70 dB
---------------	---------

PHYSICAL

Degree of protection:	IP54
------------------------------	------

COMPLIANCE

Compliance:	ISO 13849 PL «c» CAT. 2 (under the condition that the door control system monitors the sensor at least once per door cycle)
--------------------	--

DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company