



- NOTES: 1) LO21U DIPSWITCHES: #1-5 (LOCK-OUT TIMING), #6 (DOWN/ON), #7 (DOWN/ON), #8 (UP/OFF).
 2) LO-21B MAY BE SUBSTITUTED FOR THE LO-21U.
 3) SWITCH SHALL CLOSE AT APPROX. 65-70 DEGREES.
 4) REMOVE JUMPER #7 THIS ALLOWS THE BODYGUARD TO SAFETY THE DOOR.
 5) INSERT SAFETY SIDE SUPERSCAN BLUE WIRE INTO PIN 6, BROWN INTO PIN 4, WHITE INTO PIN 1.

IF AFTER TROUBLESHOOTING A PROBLEM, A SATISFACTORY SOLUTION CANNOT BE ACHIEVED, PLEASE CALL B.E.A., INC. FOR FURTHER ASSISTANCE DURING EASTERN STANDARD TIME AT 1-800-523-2462 FROM 8AM - 5PM. FOR AFTER-HOURS, CALL EAST COAST: 1-866-836-1863 OR 1-800-407-4545 / MID-WEST: 1-888-308-8843 / WEST COAST: 1-888-419-2564. DO NOT LEAVE ANY PROBLEM UNRESOLVED. IF YOU MUST WAIT FOR THE FOLLOWING WORKDAY TO CALL B.E.A., LEAVE THE DOOR INOPERABLE UNTIL SATISFACTORY REPAIRS CAN BE MADE. NEVER SACRIFICE THE SAFE OPERATION OF THE AUTOMATIC DOOR OR GATE FOR AN INCOMPLETE SOLUTION. WEB: WWW.BEASENSORS.COM

		100 ENTERPRISE DRIVE PITTSBURGH, PA 15275 PHONE: (412) 249-4100 FAX: (412) 249-4101 EMAIL: www.beasensors.com	
TITLE: BESAM POWERSWING WITH LO-21U PASSPORT PLUS PARALLAX II SYSTEM Q-DISCONNECT ON APPROACH SIDE			
SIZE: B	DRAWN BY: KJG	REV BY: WJR	PART NO: 80.0196.03
SCALE: NONE	DATE: 26 NOV 2008	SHEET: 1 OF 1	