


LO-21

RED LO21 DEFAULT DIP SWITCHES
 GREEN

OFF ON



N.C.	5
N.O.	4
green	
COM	3
white	
POWER 2	
black	
POWER 1	
red	

● 1	GND
● 2	IN
● 3	GND
● 4	IN
● 5	+24 VDC
● 6	GND
● 7	IN
● 8	GND
● 9	IN
● 10	+24 VDC
● E11	E MODULE 1 RELAY A
● E12	
● E14	

NOTE: CONNECT THE LO21 DASHED LINES (GREEN, BLUE, BLACK/WHITE, PURPLE, GRAY) ONLY IF SAFETY BEAMS ARE USED.

IF AFTER TROUBLESHOOTING A PROBLEM, A SATISFACTORY SOLUTION CANNOT BE ACHIEVED, PLEASE CALL B.E.A., INC. FOR FURTHER ASSISTANCE DURING EASTERN STANDARD TIME AT 1-800-523-2462 FROM 8AM - 5PM. FOR AFTER-HOURS, CALL EAST COAST: 1-866-836-1863 OR 1-800-407-4545 / MID-WEST: 1-888-308-8843 / WEST COAST: 1-888-419-2564. DO NOT LEAVE ANY PROBLEM UNRESOLVED. IF YOU MUST WAIT FOR THE FOLLOWING WORKDAY TO CALL B.E.A., LEAVE THE DOOR INOPERABLE UNTIL SATISFACTORY REPAIRS CAN BE MADE. NEVER SACRIFICE THE SAFE OPERATION OF THE AUTOMATIC DOOR OR GATE FOR AN INCOMPLETE SOLUTION. WEB: WWW.BEASENSORS.COM

BEA 100 ENTERPRISE DRIVE
 PITTSBURGH, PA 15275
 PHONE: (412) 249-4100
 FAX: (412) 249-4101
 EMAIL: www.beasensors.com

**TITLE: TORMAX TDA SINGLE WITH
 PARALLAX 1 SYSTEM (LO-21)**

SIZE: A	DRAWN BY: TUC	REV BY: WJR	PART NO: 80.0214.03
	SCALE: NONE	DATE: 03 FEB 2008	SHEET 1 OF 1