





SUPERSCAN QUICK DISCONNECT CABLE



BODYGUARD





DK-12



|                |
|----------------|
| Activation     |
| Activation RTN |
| Safety 1       |
| Safety RTN     |
| Safety 2       |
| 24VAC Out      |
| 24VAC Out      |
| Ground         |
| 24VAC IN       |
| 24VAC IN       |

PRELIMINARY



- NOTES:
1. BEA RECOMMENDS TO USE THE HUNTER SYNC BOARD TO SYNC 2 DOOR CONTROLS WITH A PAIR OF DOORS.
  2. REMAINING WIRES ON LO21K NOT USED.
  3. IF USING THE OPTIONAL INHIBIT SWITCH ROUTE SAFETY SIDE SUPERSCAN'S N.O. IN SERIES THRU THE INHIBIT SWITCH.

**BEA**  
We open up New Horizons  
HALMA GROUP COMPANY

**B.E.A., Inc.**  
100 Enterprise Drive Pittsburgh, PA 15275  
PH: (412) 249-4100 FAX: (412) 249-4101  
[www.beasensors.com](http://www.beasensors.com)

**Hunter Automatics FA Control, TYPE 09722A, LO21K, Parallax 2 Quick Disconnect on Approach**

|          |           |                      |          |              |     |
|----------|-----------|----------------------|----------|--------------|-----|
| SIZE     | CAGE CODE | DWG NO               | FILE OF: | DRAWN BY:    | REV |
| <b>A</b> |           | 80.0222              | JED      | JED          |     |
| SCALE    |           | DATE: 6 JUNE 24 2004 |          | SHEET 1 OF 1 |     |