



**NOTES:**

- 1) DPS 1 ON FIRST DOOR TO OPEN AND LAST DOOR TO CLOSE (DOOR 1) SWITCH IS CLOSED WHEN DOOR IS CLOSED.
- 2) DPS 2 ON LAST DOOR TO OPEN AND FIRST DOOR TO CLOSE (DOOR 2) SWITCH IS OPEN WHEN DOOR IS CLOSED.
- 3) SET RELAY 1 OUTPUT ON FIRST Br-3 SET TO FUNCTION 22 FOR DC / WET VIA JUMPERS AS SHOWN ABOVE. ENSURE SECONDD Br-3 (FUNCTION 28) RELAY 1 IS SET TO DEFAULT DRY OUTPUT
- 4) DRY CONTACT ONLY. IF KEYPAD IS A WET OUTPUT CONNECT TO THE WET INPUT OF BR-3.
- 5) IF USING A UL MAGLOCK ENSURE THE POWER SUPPLY IS A UL POWER SUPPLY. BEA PT # 10PS1224

**BEA**  
OPEN UP NEW HORIZONS  
A HALMA GROUP COMPANY

100 ENTERPRISE DRIVE  
PITTSBURGH, PA 15275  
PHONE: (412) 249-4100  
FAX: (412) 249-4101  
EMAIL: www.beasensors.com

**TITLE:** BR-3 NON SIM. PAIR W/ MAG-LOCK, SUPER SCAN INHIBIT AND REACTIVATION DELAY INHIBIT.

SIZE: <b>A</b>	DRAWN BY: WJR	REV BY:	PART NO: <b>80.0316.00</b>
	SCALE: NONE	DATE: 01 06 2009	SHEET 1 OF 1