



DELAYED EGRESS MAGLOCK KIT

UL LISTED ALL-IN-ONE KIT WITH MAGLOCK,
SOUNDER AND KEYSWITCH



PRODUCT



[Go to the product page](#)

CERTIFICATIONS



DESCRIPTION

BEA's **DELAYED EGRESS MAGLOCK KIT** is a user friendly security solution for out-swinging perimeter doors. The kit meets a variety of building, fire and life safety codes.

A 1,200 lb, pressure-sensing maglock is coupled with a keyswitch and sounder to create an easy-to-install solution that controls and monitors door access.

The keyswitch can be positioned in a convenient location to create authorized personnel access points.

*Not intended for outdoor environments



Door Synchronizing Feature

Double door (2 single doors) can be synchronized

Programmable Egress Time

Authorized egress time programmable 0 – 15 seconds

Selectable Alarm

Selectable 30 second door prop alarm

Customizable LED Features

LED color and flashes can be customized

Input Features

Monitored fire alarm input

Triggering Options

Delayed Egress can be triggered with pressure on the door or with a REX input (or disabled completely)

Standards Compliant

UL 294 listed kit

TECHNICAL SPECIFICATIONS

Housing Dimensions	10.8215" (W) × 2.875" (H) × 2.125" (D)
Armature Dimensions	7.4375" (W) × 2.375" (H) × 0.625" (D)
Voltage / Tolerance	12 – 24 VDC; ±10%
Max. Power / Current Draw	
Maglock & Sounder	0.49 A / 12 VDC 0.24 A / 24 VDC
Low Voltage Supply Detection / Alarm	< 8 V
Holding Force	Up to 1200 lb
Mortise Cylinder	1 1/8" cylinder with straight cam required, NOT INCLUDED
	Requires Part 10CYLINDERKA or 10CYLINDERKD
Operating Temperature	14 – 140 °F
Norm Conformity	UL / CUR Listed FWAX Special locking arrangements
Compliance Provisions	IBC, SBC, UBC, BOCA, or NBC of Canada, NFPA 101

PRODUCT SERIES



10MAGDE1
DELAYED EGRESS
MAGLOCK KIT



10CYLINDERKA
Mortise cylinder /
keyed alike



10CYLINDERKD
Mortise cylinder /
keyed different



10KEYPADU
UNIVERSAL KEYPAD



10KEYPADUSL
UNIVERSAL SLIM-LINE
KEYPAD



10PS12-24
UL / ULC Listed power
supply

DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A **Halma** company