



LED SIGNAL MODULAR LIGHTS

UL LISTED BUILD-YOUR-OWN LIGHTS AND AUDIBLE ALARM



PRIMARY APPLICATIONS



DESCRIPTION

BEA's LED Signal Modular Lights and Audible Alarm series is part of a portfolio of warning indication products, including BEA activation, safety and presence sensors. These signal lights integrate seamlessly into industrial automation and vehicle flow management applications.

LED Signal Modular Lights offer customizable configurations with "build-your-own" lighting elements that share a common base and bracket. These LED signal units are available in red, green, yellow and an audible alarm cap and can be stacked in a tower configuration with up to six modules.

FEATURES & BENEFITS


- UL Listed
- NEMA 4 / IP65
- Light units can be programmed to pulse at a rate of 1.5 or 3 times per second or remain steady
- Optional audible alarm unit offers secondary alert method with chirp, siren, continuous and 1.5 beeps-per-second configuration settings
- Base unit and bracket are designed for a variety of installations
- BEA can create custom integrations for any safety, automation or flow management application



BEA, Inc.
RIDC Park West
100 Enterprise Drive
Pittsburgh, PA 15275-1213

Customer Service: 800.523.2462
Technical Support: 800.407.4545
www.BEAinc.com


APPLICATIONS



TECHNICAL SPECIFICATIONS

Supply Voltage	12 – 30 VDC
Indicator Response Time	
Off Response	150 μ s @ 12 – 30 VDC
On Response	180 mSec @ 12 VDC; 50 mSec @ 30 VDC
LED Colors	Red, Green, Yellow
Light Flash Rates	1.5 Hz \pm 10% and 3 Hz \pm 10%
Audible Alarm	2.6 KHz \pm 250 Hz oscillation frequency; maximum intensity 92 dB @ 39.6 in
Audible Adjustment	Rotate the alarm cover; Open to closed is 8 dB
Connector	78 in, 8-wire integral cable
Operating Temperature	-40 °F – 122 °F 95% @ 122 °F maximum relative humidity (non-condensing)
Degree of Protection	NEMA 4 / IP65
Norm Conformance	CE, UL 1598 Listed and UL 8750 Listed
Dimensions	
Base	2.75 in ϕ x 1.38 in (H)
Light Segment	2.75 in ϕ x 2.38 in (H)
Audible Segment	2.75 in ϕ x 2.75 in (H)

RELATED PRODUCTS



10LIGHT-TBASE
MODULAR LED
SIGNAL BASE



10LIGHTBRACKET-TL70
MODULAR
LED SIGNAL
LIGHT BRACKET



10LIGHT-TR
MODULAR LED
SIGNAL LIGHT
SEGMENT-RED



10LIGHT-TG
MODULAR LED
SIGNAL LIGHT
SEGMENT-GREEN



10LIGHT-TY
MODULAR LED
SIGNAL LIGHT
SEGMENT-YELLOW



10LIGHT-A
MODULAR
LED SIGNAL
AUDIBLE SEGMENT



10BR3
LOGIC
MODULE



10LZR30
PRESENCE
SENSOR



10FALCON
MOTION
SENSOR



10BEAMBOX
INFRARED
PRESENCE SENSOR



10SPARROW
MOTION
SENSOR



10PS1224
12 OR 24 VDC
POWER SUPPLY

www.BEAinc.com

© 2017 BEA, Inc. All rights reserved.

LED SIGNAL MODULAR LIGHTS UL LISTED BUILD-YOUR-OWN LIGHTS AND AUDIBLE ALARM

