



NOTES:

SET BR3 TO FUNCTION 25.
RECOMMENDED BR3 SETTINGS H1=01, H2=10, DI=00

ONE/SINGLE SHOT EXPLANATION:

WHEN THE INPUT TRIGGER IS APPLIED (INPUT 1 & GND), THE OUTPUT ON R1/H1 IS ENERGIZED FOR 1 SEC (H1=01) IN THIS EXAMPLE AND THE R2/H2 TIME DELAY BEGINS. DURING THE R2/H2 TIME DELAY (0 – 60 SEC), THE TRIGGER IS IGNORED. AT THE END OF THE R2/H2 TIME DELAY, THE INPUT TRIGGER IS READY TO ACCEPT ANOTHER TRIGGER.

IF AFTER TROUBLESHOOTING A PROBLEM, A SATISFACTORY SOLUTION CANNOT BE ACHIEVED, PLEASE CALL B.E.A., INC. FOR FURTHER ASSISTANCE DURING EASTERN STANDARD TIME AT 1-800-523-2462 FROM 8AM - 5PM. FOR AFTER-HOURS, CALL EAST COAST: 1-866-836-1863 OR 1-800-407-4545 / MID-WEST: 1-888-308-8843 / WEST COAST: 1-888-419-2564. DO NOT LEAVE ANY PROBLEM UNRESOLVED. IF YOU MUST WAIT FOR THE FOLLOWING WORKDAY TO CALL B.E.A., LEAVE THE DOOR INOPERABLE UNTIL SATISFACTORY REPAIRS CAN BE MADE. NEVER SACRIFICE THE SAFE OPERATION OF THE AUTOMATIC DOOR OR GATE FOR AN INCOMPLETE SOLUTION.WEB: WWW.BEASENSORS.COM

	100 ENTERPRISE DRIVE
	PITTSBURGH, PA 15275
	PHONE: (412) 249-4100
	FAX: (412) 249-4101
	EMAIL: www.beasensors.com

TITLE: BR3-ONE SHOT TIMER W/KEY PAD.

SIZE: A	DRAWN BY: WJR	REV BY:	PART NO: 80.0347.00
	SCALE: NONE	DATE: 28 March, 2012	SHEET 1 OF 1