



MS41

STAINLESS STEEL, TOUCHLESS ACTUATOR WITH ADJUSTABLE RANGE AND RELAY HOLD TIME


DESCRIPTION

BEA's **MAGIC SWITCH® Family** provides a highly accessible and germ-free door activation without physical contact. Reduce touchpoints in fast-paced environments that depend on sanitation like healthcare, retail, industrial and commercial settings.


Using microwave technology, BEA's **MS41** produces a detection field with a reliable and consistent transmission in interior and exterior applications. Capable of detecting a moving hand, cart or wheelchair. Plus, an adjustable hold time offers flexibility to meet ANSI standards.

The **MS41** features rounded corners and a customizable illuminated ring with audible signaling. The durable design suits sterile, wash-down applications such as surgical, wash-down, clean room and pharmaceutical environments.


APPLICATIONS




Healthcare Environments



Clean Rooms and Sterile Facilities



Washdown Resistant




TECHNICAL SPECIFICATIONS

Technology	Microwave Doppler Radar
Radiated Frequency	24.125 GHz
Radiated Power Density	< 5 mW/cm ²
Detection Mode	Motion (bidirectional)
Detection Range	4 – 24" (adjustable)
Output	Relay with switch-over contact (voltage-free)
Max. Contact Voltage	60 VDC / 125 VAC
Max. Contact Current	1A (resistive)
Max. Switching Power	30W DC / 60 VAC
Output Hold Time	0.5 – 30 s
Supply Frequency	50 – 60 Hz
Supply Voltage	12 – 24 VAC ±10%, 12 – 24 VDC +30% / -10%
Power Consumption	< 1.5 W
Weight	0.34 lbs
Material	Stainless Steel
Temperature Range	-4 – 131 °F
IP Rating*	IP55
	Apply silicone to achieve IP65
Dimensions**	
Single Gang	4 ½" (H) × 2 ¾" (W) × ⅝" (T)
Double Gang	4 ½" (H) × 4 ½" (W) × ⅝" (T)
Round	6" (D) × ⅝" (T)
Cube	2.047" (H) × 2.047" (W) × 1.093" (T)
Certification	EMC: 2004 / 108 / EC FCC: G9B-210161 IC: 4680A-210161

* See Users Guide

** MS41 is not compatible with some metallic cut-in electrical boxes. Please check cube dimensions prior to installation.



DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company